Handheld POS

SUNMI V2 PF





reddo t design award



Industry-first full screen 5.99" handheld POS terminal.

Designed by a world-famous master. The thinnest part only measures 13mm.

58mm thermal receipt printing and label printing available.

Equipped with a professional 2D barcode scan engine and an NFC module.

4G connectivity; Wi-Fi 2.4G/5G; vSIM.







Handheld Ordering



Online Order Receiving



Label Printing



Item Management



Queue Management



Scan to Redeem Coupons



PSAM





SUNMI V2 PRO

Tech Specs

V2 PRO

1D barcode scan engine; 58mm thermal receipt printing.



V2 PRO Label Version

2D barcode scan engine; 58mm thermal receipt printing/label printing.



Standard Configurations

os os

Android 7.1 SUNMI OS Printer



7)

CPU

Corte-A53, quad-core 1.4GHz

NFC Card Reader

Supports Type A&B card Mifare card Felica card; ISO/ICE 14443 and



Memory

Scanner

Battery



口)

Display

Speaker

5.99"HD+, 1440*720



5MP AF + Flashlight Card Slot

Rear Camera

1* PSAM 1* MINI SIM

vSIM

Network

2G & 3G & 4G



2.4GHz/5GHz Supports IEEE 802.11 a/b/g/n



Supports Bluetooth 2.1/3.0/4.2 Supports BLE



Supports AGPS Supports GPS, Glonass, Beidou



Buttons

Built-in 58mm thermal printer Print speed: 70mm/s Paper roll: Ф40mm



Ports 1* Type-C Supports OTG

Cradle (Optional)

Non-removable lithium polymer battery; 7.6V/2580mAh





Total Weight



Environment Operating temperature: 0°C~45°C Storage temperature: -40°C~70°C



Supports charging and has a USB port

Label Version Configurations



Printer

Built-in 58mm thermal printer; Paper roll: Φ40mm Print speed (receipt/label): 70mm/s Label paper specs: 50~58mm wide, ≥20mm high, 2mm wide gap







Actual memory will be reduced due to a number of factors and may vary. Operating system also occupies some memory.

The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.